

MIXER FLATSPRAY 15

Airless atomizers | reference : 3B03207000



Mixer Flatspray 15 allows for the application of all types of thin film coatings. It is a compact, quiet and light machine.

It can be moved up and down stairs by only one person, thanks to its trolley-type chassis.

The cleaning procedure is quick and only has to be done at the very end of the project.

The pump can be changed in 5 minutes directly on the construction site.

TECHNICAL DATA

Maximum working pressure	120 bar
Maximum product flow-rate	6/L min*
Electric motor	2,2 kW
Power	230 V / 50 and 60 Hz
Type of pump	volumetric screw pump
Pump	JET 2
Tank capacity	57 L
Max grain size	1 mm
Dimensions (l x w x h)	113 x 61 x 78 cm
Weight	62 kg

(*) depending on the characteristics of the product used, the stator, the rotor, the diameter and length of the hose, the spraying height and the ambient temperature.

DELIVERED WITH

- a 10 M Hose
- a spray-gun with nozzle holder
- a 443 nozzle
- 1 toolbox containing:
 - a 17 spanner
 - two open-end wrenches 22/32 and 27/38
 - a multigrip pliers
 - three Allen keys Ø2, 5 and 8
 - two cleaning balls and a cleaning brush
 - 1 L of storage liquid

MIXER[®]